



AIA STANDARDS MEMORANDUM

April 30, 2025

TO: National Aerospace Standards Committee (A6)

FROM: Drake McGregor

SUBJ: NAS/NASM Mailing 25-04

NAS No.	Date	Rev	Status	Project/Custodian	3D	Title
NA0036	April 30, 2025	7	**	P2405AIA	Y	BOLT, CLOSE TOLERANCE, HEXAGON HEAD, ALLOY STEEL, 1100 MPa, METRIC
NA0155	April 30, 2025	4	**	P2415AIA	Y	BOLT, CLEVIS, 660 MPa SHEAR, METRIC
NAS1034-NAS1038	April 30, 2025	7	R,S	P755AIA-25112S	N	NUT ASSEMBLY, SELF-LOCKING, GANG CHANNEL, REGULAR HEIGHT, NON-CSK
NAS1413	April 30, 2025	11	**	P2341AIA	N	PINS AND COLLARS, SWAGE LOCKING
NAS1473	April 30, 2025	13	**	P2391HFS	Y	NUT, SELF-LOCKING, PLATE, TWO LUG, CAP, FLOATING
NAS1712	April 30, 2025	9	**	P2170AIA	Y	CLAMP, LOOP, CUSHIONED, RECTANGULAR
NAS1737	April 30, 2025	2	**	P755AIA-17321	N	SEATING TORQUE LIMITS FOR 160 KSI THREADED FASTENER SYSTEMS WITH DOVETAIL SLOT, OFFSET CRUCIFORM, OR TRI-SLOT RECESS, SUBJECT TO PERIODIC REMOVAL
NAS1794	April 30, 2025	5	**	P2282AIA	Y	NUT, SELF-LOCKING, COUNTERBORE REPLACEABLE ELEMENT
NASM1312-5	April 30, 2025	1	R,S	P755AIA-25113S	N	FASTENER TEST METHODS METHOD 5 STRESS DURABILITY
NASM1312-6	April 30, 2025	1	R,S	P755AIA-25114S	N	FASTENER TEST METHODS, METHOD 6, HARDNESS
NASM1312-8	April 30, 2025	3	**	P2512AIA	N	FASTENER TEST METHODS, METHOD 8, TENSILE STRENGTH

NASM8975/1	April 30, 2025	1	R,S	P755AIA-25115S	N	FASTENERS, BLIND, HIGH STRENGTH, INSTALLATION FORMED, CORROSION RESISTANT AND HEAT RESISTANT STEEL AND TITANIUM, DESIGN AND USAGE LIMITATIONS FOR
NASM14164	April 30, 2025	1	R,S	P755AIA-25116S	Y	NUT, WHEEL, SELF-LOCKING, FLANGED, STEEL, 220 KSI Ftu, 450 °F, SPLINE DRIVE
NASM14181	April 30, 2025	9	**	P2515AIA	Y	BOLT, TENSION, NICKEL ALLOY 718, 220 KSI Ftu, EXTERNAL WRENCHING, SPLINE DRIVE, FLANGED HEAD
NASM16205	April 30, 2025	1	R,S	P755AIA-25117S	Y	BOLT, MACHINE, REGULAR SEMI-FINISHED HEXAGON HEAD, COPPER-SILICON ALLOY (SILICON BRONZE), UNC-2A, NON-MAGNETIC
NASM16491/2	April 30, 2025	2	R,S	P755AIA-25103S	N	GROMMET, METALLIC, OBLONG, WITH FLAT WASHER (TYPE IV)
NASM21068	April 30, 2025	1	R,S	P755AIA-25118S	Y	NUT, SELF-LOCKING, GANG CHANNEL, 100° CSK, FLOATING, LOW HEIGHT, CRES, 125 KSI Ftu, 450 °F & 800 °F
NASM21332	April 30, 2025	2	**	P755AIA-17159	N	FASTENER, SNAPSLIDE
NASM45938/9	April 30, 2025	1	R,S	P755AIA-25119S	Y	NUT, SELF-LOCKING, CLINCH, SWAGE-CLINCHING, KNURLED SHANK, 250 °F, UNJF-3B
NASM63540/5	April 30, 2025	1	R,S	P755AIA-25120S	N	STUD, SELF-LOCKING, CONCEALED HEAD, HEX CLINCH TYPE

Status Legend:

**	New Revision	*	Inactive for New Design
+	New Standard	X	Cancelled
R	Reaffirmed	RA	Reactivated
S	Stabilized	A	Amendment

Enclosures

cc: NASC A1, A2, A3 (without enclosures)