



## AIA STANDARDS MEMORANDUM

July 31, 2025

TO: National Aerospace Standards Committee (A6)  
Quality Assurance Committee

FROM: Drake McGregor  
SUBJ: NAS/NASM Mailing 25-07

NAS No.	Date	Rev	Status	Project/Custodian	3D	Title
NA0060	July 31, 2025	6	**	P2322AIA	Y	SCREW, CLOSE TOLERANCE, 100° FLUSH HEAD, OFFSET CRUCIFORM RECESS, ALLOY STEEL, 750 MPa SHEAR, METRIC
NA0179	July 31, 2025	2	**	P755AIA-17235	Y	WASHER, PLAIN AND COUNTERSUNK, METRIC
NAS414	July 31, 2025	NEW	+	Q011	N	USE OF SUPPLIER'S "QUALITY" METRICS TO OPTIMIZE SECOND PARTY SURVEILLANCE METHODS
NAS1202-NAS1210	July 31, 2025	12	**	P755AIA-18203	Y	BOLT, 100° CLOSE TOLERANCE HEAD AND SHANK, 160,000 PSI, SHORT THREAD
NAS1368	July 31, 2025	9	R,S	P755AIA-25212S	Y	GROMMET, PLASTIC FLIP TYPE
NAS1675	July 31, 2025	7	**	P755AIA-25223	N	FASTENER, BLIND, INTERNALLY THREADED, EXTERNAL SLEEVE SELF-LOCKING
NAS1759	July 31, 2025	4	**	P755AIA-25226	Y	NUT, SELF-LOCKING, DOUBLE HEXAGON, SHEAR, 450 °F
NAS1829	July 31, 2025	6	**	P755AIA-18211	Y	POST, ELECTRICAL, MECHANICAL EQUIPMENT, STUD TYPE
NAS9800	July 31, 2025	4	R, S	P755AIA-25213S	N	HEAD PROTRUSION GAGING, 100° FLUSH HEAD FASTENERS, GAGE BLOCK, GAGE DIAMETERS AND STYLUS
NASM970	July 31, 2025	3	**	P2178AIA	Y	WASHER, FLAT
NASM1312-9	July 31, 2025	1	R, S	P755AIA-25214S	N	FASTENER TEST METHODS METHOD 9 STRESS CORROSION
NASM1312-14	July 31, 2025	1	R, S	P755AIA-25215S	N	FASTENER TEST METHODS METHOD 14 STRESS DURABILITY, INTERNALLY THREADED
NASM14531	July 31, 2025	2	R, S	P755AIA-25217S	Y	PIN, QUICK RELEASE WITH WARNING STREAMER ASSEMBLY
NASM18063	July 31, 2025	2	**	P2516AIA	Y	SETSCREW, HEXAGON SOCKET, CUP POINT, 250 °F, SELF LOCKING ELEMENT, ALLOY STEEL, CADMIUM PLATED AND ZINC-NICKEL PLATED

NASM21073	July 31, 2025	3	**	P755AIA-17337	Y	NUT, SELF-LOCKING, PLATE, CORNER, REDUCED RIVET SPACING, LOW HEIGHT, STEEL, 125 KSI Ft <sub>u</sub> , 450 °F
NASM21084	July 31, 2025	3	**	P755AIA-22329	Y	NUT, SELF-LOCKING, STEEL, 220 KSI Ft <sub>u</sub> , 450 °F, FLANGED, MS33787 WRENCHING ELEMENT
NASM24661	July 31, 2025	2	**	P755AIA-16430	Y	RIVET, BLIND, COUNTERSUNK HEAD, DRIVE TYPE
NASM33537	July 31, 2025	4	**	P2259AIA	N	INSERT, SCREW THREAD, HELICAL COIL, INCH SERIES, COARSE AND FINE THREAD, STANDARD ASSEMBLY DIMENSIONS FOR
NASM33557	July 31, 2025	2	R, S	P755AIA-25219S	N	NONSTRUCTURAL RIVETS FOR BLIND ATTACHMENT; LIMITATIONS FOR DESIGN AND USAGE
NASM35792	July 31, 2025	2	**	P755AIA-17231	N	HANDLE, BAIL, CHEST, RECESSED
NASM43770/8	July 31, 2025	1	R, S	P755AIA-25220S	N	SNAP HOOK, CAST BODY, ROUND EYE SWIVEL
NASM45938/14	July 31, 2025	3	**	P755AIA-25227	Y	NUT, PLAIN, CLINCH AND NUT, SELF-LOCKING, CLINCH, SELF-CLINCHING, KNURLED COLLAR, FLOATING, 450 °F AND 600 °F
NASM51605	July 31, 2025	2	**	P755AIA-17232	N	PIN, GROOVED, HEADLESS, HALF LENGTH TAPER GROOVE, CRES
NASM51964	July 31, 2025	4	**	P755AIA-18307	Y	SETSCREW, HEXAGON SOCKET, CUP POINT, ALLOY STEEL, CADMIUM AND ZINC-NICKEL PLATED, UNF-3A, PLAIN AND SELF-LOCKING

Status Legend:

**	New Revision	*	Inactive for New Design
+	New Standard	X	Cancelled
R	Reaffirmed	RA	Reactivated
S	Stabilized	A	Amendment

Enclosures

cc: NASC A1, A2, A3 (without enclosures)