



AIA STANDARDS MEMORANDUM

December 31, 2025

TO: National Aerospace Standards Committee (A6)

FROM: Drake McGregor
 SUBJ: NAS/NASM Mailing 25-13

NAS No.	Date	Rev	Status	Project/Custodian	3D	Title
NA0084	December 31, 2025	5	**	P755AIA-24156	Y	NUT, SELF-LOCKING, PLATE, FIXED, SIDE BY SIDE, CRES REDUCED RIVET SPACING, LOW HEIGHT, CBORE, 900 MPa, METRIC, 235 °C AND 425 °C
NA0140-NA0144	December 31, 2025	2	**	P2142AIA	Y	WASHER, DIMPLED, 100°, METRIC
NA0146	December 31, 2025	3	**	P755AIA-24204	Y	INSERT, SCREW THREAD, KEY LOCKED, ALLOY STEEL, MINIATURE, METRIC
NA0184	December 31, 2025	3	**	P755AIA-22250	N	SPACER, NUT, PLATE, UNIVERSAL, METRIC
NAS73	December 31, 2025	11	**	P2558AIA	N	BUSHING, CLAMP-UP, STEEL, CADMIUM AND ZINC-NICKEL PLATED
NAS74	December 31, 2025	8	**	P755AIA-19101	Y	BUSHING, CLAMP-UP, ALUMINUM-SILICON BRONZE
NAS77	December 31, 2025	16	**	P2226AIA	Y	BUSHING, FLANGED, PRESS FIT STEEL, CRES, BRONZE, ALUMINUM BRONZE & COPPER
NAS537	December 31, 2025	11	**	P2359AIA	Y	BUSHING, SLEEVE, PRESS FIT, UNDERSIZE INSIDE DIAMETER
NAS1720	December 31, 2025	5	**	P2508HFS	Y	RIVET, BLIND, PROTRUDING HEAD, MECHANICALLY LOCKED SPINDLE
NAS1774	December 31, 2025	4	**	P2553AIA	N	NUT, SELF-LOCKING, PLATE, ONE LUG, LOW HEIGHT, CBORED, FLOATING, 160 KSI, 450 °F, 800 °F
NAS1778	December 31, 2025	3	**	P2546AIA	Y	NUT, SELF-LOCKING, PLATE, ONE LUG, LOW HEIGHT, CBORED, SIDE BY SIDE, 160 KSI, 450 °F, 800 °F
NAS1838	December 31, 2025	3	**	P755AIA-20431	N	INSERTS, SCREW THREAD, METALLIC, KEYRING LOCKED, SPECIFICATION FOR
NAS2832-NAS2840	December 31, 2025	5	**	P2064AIA	Y	BOLT, 100° FLAT HEAD, RIBBED OFFSET CRUCIFORM AND DOVETAIL SLOT, 180 KSI
NAS5319	December 31, 2025	4	**	P1911AIA	Y	SCREW, SHEAR, 100 DEG FLUSH HEAD, CLOSE TOLERANCE, NAS1800 SIX LOBE RECESS, 95 KSI Fsu
NAS6603-NAS6620	December 31, 2025	11	**	P2417AB	Y	BOLT, TENSION, HEX HEAD, CLOSE TOLERANCE, ALLOY STEEL, LONG THREAD, REDUCED MAJOR DIA., SELF-LOCKING AND NONLOCKING, 160 KSI Ft _u
NAS8200-NAS8206	December 31, 2025	4	**	P755AIA-24418	Y	SCREW, PAN HEAD, RIBBED CRUCIFORM RECESS, TITANIUM ALLOY 6AL-4V, FULL THREAD, SELF-LOCKING AND NONLOCKING



NASM21098	December 31, 2025	3	**	P2376AIA	Y	BOLT, SELF-LOCKING, STEEL, 160 KSI Ft _u , 250 °F, 12 POINT, EXTERNAL WRENCHING (EXTERNALLY WRENCHING CAP SCREWS)
NASM24665	December 31, 2025	3	**	P2228AIA	Y	PIN, COTTER (SPLIT)
NASM51833	December 31, 2025	3	**	P2377AIA	Y	STUD, LOCKED IN, KEY-LOCKED, LIGHTWEIGHT
NASM90726	December 31, 2025	3	R	P2406AIA	Y	SCREW, CAP, HEXAGON HEAD (FINISHED HEXAGON BOLT), STEEL, GRADE 5, CADMIUM PLATED, UNF-2A

Status Legend:

**	New Revision	*	Inactive for New Design
+	New Standard	X	Cancelled
R	Reaffirmed	RA	Reactivated
S	Stabilized	A	Amendment

Enclosures

cc: NASC A1, A2, A3 (without enclosures)